

General features for MPPS Series battery (OPzS)

- * Tubular positive plate; separator with the combined application of porous rubber and porous PVC, separator is with a high porosity & good corrosion resistance.
- * Computer designed lead, calcium tin alloy grid for high power density.
- * Long service life, float or cyclic applications: designed floating life is 20 years at 25°C; Designed cycle life more than 1200 cycles at 80% DOD at 25°C/77°F.
- * Acid-proof bolt: It is of a special shape of funnel having the function of filtering acid smog and retarding flame, it can measure the density and temperature of electrolyte.
- * Ensuring sufficient electrolyte for battery discharge.
- * Battery container is transparent, easy checks electrolyte.



Maxton Power Tech Co., Ltd
www.maxtonpower.com
info@maxtonpower.com

MPPS2-800 (2V800Ah)


Specifications

Nominal Voltage		2 V
Rated capacity (10 hour rate)		800 Ah
Dimensions (±3mm)	Total Height (Include terminal)	700mm (27.6inches)
	Height	645mm (25.4inches)
	Length	191mm (7.52inches)
	Width	210mm (8.3inches)
Approx Weight (±5%)	Without electrolyte	44.0Kg (97.0lbs)
	With Electrolyte	60.0Kg (132.3lbs)
	Electrolyte weight (d=1.25kg/l)	Approx 16Kg (35.3lbs)

Battery picture and construction




Connection method for reference:



Battery Construction

Component	Positive plate	Negative plate	Container	Cover
Raw material	Lead dioxide	Lead	SAN transparent	SAN
Component	Electrolyte	Separator	Safety valve	Terminal
Raw material	Dilute sulfuric acid	PVC	Porous rubber	Copper

Outer dimension and terminal



Characteristics

Capacity 25°C(77°F)	10 hour rate(80A, 1.8V)	800Ah
	3 hour rate(205.6A, 1.75V)	616.8Ah
	1 hour rate(448A, 1.60V)	448Ah
Internal Resistance	Full charged battery at 25°C(77°F)	Approx 0.5 mΩ
Capacity affected by Temperature (10hour rate)	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	85%
Remaining capacity Self-Discharge At 25°C(77°F)	Capacity after 3 month storage	≥ 88%
	Capacity after 6 month storage	≥ 76%
Terminal type		TP (copper)
Max. Discharge current 25°C/(77°F)		4000A (5Seconds)
Nominal operating temperature		25°C ± 5°C (77°F ± 9°F)
Operating Temperature Range	Discharge	-15°C ~ 50°C (5°F ~ 122°F)
	Charge	0°C ~ 45°C (32°F ~ 113°F)
	Storage	-15°C ~ 45°C (5°F ~ 113°F)
Charge methods (constant Voltage) At 25°C(77°F)	Boost charge	Initial Charging Current less than 200A Voltage 2.35-2.45V Temperature compensation:-3mV/°C
	Floating charge	Voltage 2.25-2.30V Temperature compensation:-3mV/°C

Constant current discharge (25°C , 77 °F)

Unit:A

Constant power discharge (25°C , 77 °F)


Unit:watts

Constant Current(Amp) and Constant Power(Watt) Discharge Table at 25°C (77°F)


Time		30min	1h	2h	3h	5h	6h	8h	10h	20h	24h	48h	100h
		1.65V	A	570.7	442.5	290.7	218.4	149.1	120.6	102.4	84.5	45.7	38.3
	W	1197	904	653	437	293	272	232	167	87.0	78.3	51.8	26.9
1.70V	A	547.6	424.2	284.0	212.4	145.9	118.3	100.4	83.2	45.2	38.1	20.4	10.1
	W	1111	879	647	435	288	264	228	165	86.1	77.6	51.7	26.8
1.75V	A	506.9	402.7	268.0	205.6	142.1	115.7	98.8	81.9	44.4	38.0	20.1	10.0
	W	994	851	643	428	284	258	224	164	85.2	76.8	51.6	26.6
1.80V	A	450.7	370.7	253.3	195.2	136.0	112.9	94.3	80.0	43.2	37.9	20.0	9.9
	W	816	771	628	414	279	256	216	160	84.5	76.0	51.5	26.5
1.85V	A	360.0	317.3	232.0	178.7	127.7	107.6	88.8	75.6	40.8	36.1	19.8	9.9
	W	601	678	573	383	270	252	207	156	83.2	72.6	51.3	26.4

(Above characteristics data are average values obtained within three charge/discharge cycles, not the minimum values.)


Discharge characteristics (25°C, 77°F)




Charge characteristics (25°C, 77°F)




Life characteristics of Cyclic Use (25°C, 77°F)




Effect of Temperature on capacity




Self-discharge characteristics (with full charging)




Initial charging characteristics



Relationships for open voltage and remained capacity (for reference)



Relationship for service life and temperature



Effect of discharge rate on capacity

