

General features for MPSS Series (AGM Start-Stop Battery)

- * Advanced Absorbed Glass Mat (AGM) technology.
- * Maintenance-free design.
- * Durable, longer cycling life than ordinary batteries.
- * Excellent charging acceptance and fast recharging.




Maxton Power Tech Co., Ltd
www.maxtonpower.com
info@maxtonpower.com

MPSS12-60 (12V60Ah)




Outer dimensions (mm)



Specifications

Nominal Voltage		12 V
Rated capacity (20 hour rate)		60Ah
Dimensions	Total Height	190mm (7.48 inches)
	Height	190mm (7.48inches)
	Length	242mm (9.53 inches)
	Width	175mm (6.89 inches)
Weight Approx		18.2Kg (40.0 lbs)


Terminal Type (mm)




Characteristics

Capacity 25°C(77°F)	20 hour rate(2.75A) Reserve capacity(25A) CCA(-18°C)	60AH 100min 660A
Capacity affected by Temperature (10hour rate)	40°C(104°F) 25°C(77°F) 0°C(32°F) -15°C(5°F)	102% 100% 85% 65%
Self-Discharge at 25°C(77°F)	Capacity after 3 month storage Capacity after 6 month storage Capacity after 12 month storage	91% 82% 64%
Charge (constant Voltage)	Initial Charging Current less than 18 A Voltage 14.40-14.80V	

Discharge Curves 25°C(77°F)



Charging characteristics(25°C)



Curves of service life and ambient temperature

